

# Interlocking Flyable LCD Video Wall System

MODULAR FLYING VIDEO WALL FRAME SYSTEM

NEC X551 UN



**Assemble and fly large concert quality and seamless video walls, quickly and securely using the Adaptive's load-rated modular LCD framing system for NEC X551 UN LCD monitors.**

Precision-machined connecting bars and compression locks link multiple LCD frames together, horizontally and vertically into a rigid framework that supports multiple LCD's. Precisely dimensioned mounting frames and LCD monitors are assembled in tiers, up to 8 deep and then the assembly is flown utilizing a loadrated rigging beam and suspension component system.



Rated for indoor use.

**Adaptive Technologies Group**  
1635 E. Burnett Street | Signal Hill, CA 90755 USA  
Ph: 562.424.1100 | Fax: 562.424.3520  
[www.adapttechgroup.com](http://www.adapttechgroup.com)



#### **ALWAYS INSTALL SAFETY CABLES**

**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.

# Interlocking Flyable LCD Video Wall System

2 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

## NEC X551 UN

As each tier is assembled, LCDs are loaded into slotted tracks that lock the LCD's into a nearly seamless position. Completed tiers are secured to the overhead rigging beam or to an upper tier, eliminating the substantial hours required to assemble and align traditional video walls.

Disassembling video walls is just as easy and safe through the use of quick release aircraft pins and custom handles.

## Rigging Beams in Landscape Orientation



Connect frames horizontally



Load LCD's into frames



Assemble Rigging Beam to frames



Hoist first tier above assembly area



Assemble next tier



Assemble next or last tier

### Features:

- Expands horizontally and vertically.
- Landscape or portrait orientations.
- Load-rated Rigging Beams from 1 column to 5 columns and up to 8 monitors deep.
- Rigging Beam also secures to bottom of video wall for tilting.
- Cam-style compression locks provide seamless alignment between LCDs.
- Precision-machined connecting bars provide rugged overhead lifting and alignment.
- Powder-coated welded alloy steel frames.
- Quick-release locking pins make setup and teardown fast and simple.
- Optional free-standing leg supports makes setup easier and more predictable.



Fly and aim assembled video wall



Rated for indoor use.

### ALWAYS INSTALL SAFETY CABLES

**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.

# Interlocking Flyable LCD Video Wall System

3 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

## NEC X551 UN

### CONFIGURATIONS

The following configurations represent popular video display patterns, but many more variables are available. Contact our applications department for assistance in designing a custom display that assures a safe and easy to install video wall.

### 1 X 4 Flying Video Wall (Landscape)


#### 1 wide by 4 deep LCD's (8 Deep Maximum)

FOR PERMANENT INSTALLATIONS

|        |                 |   |
|--------|-----------------|---|
| 4 pcs. | MVFS-X551-T     | LCD Frame                                       |
| 1 pc.  | MVFS-X551-X1RBL | 1-Way Rigging Beam                              |
| 2 pcs. | MVFS-1.5X2-SME  | Shackle Mount                                   |
| 1pc.   | MVFS-X551-X4RBP | Rigging beam portrait<br>(used as a back brace) |

#### OPTIONAL (ADD THE FOLLOWING KITS FOR STAGING AND RENTALS)

|        |                 |   |
|--------|-----------------|---|
| 4 pcs. | MVFS-025-T-QRP  | 8pcs 1/4" Quick Release Pin / lanyard kit |
| 1 pc.  | MVFS-1.5-X1QRP  | 2pcs 1/4" Quick Release Pin / lanyard kit |
| 2 pcs. | MVFS-375-ME-QRP | 2pcs 3/8" Quick Release Pin / lanyard kit |



### 1 X 2 Flying Video Wall (Portrait)


#### 1 wide by 2 deep LCD's (8 Deep Maximum)

FOR PERMANENT INSTALLATIONS

|        |                 |  |
|--------|-----------------|--|
| 2 pcs. | MVFS-X551-T     | LCD Frame                              |
| 1 pc.  | MVFS-X551-X1RBP | 1-Way Rigging Beam                     |
| 2 pcs. | MVFS-1.5X2-SME  | Shackle Mount                          |
| 1pc.   | MVFS-X551-X2RBL | Rigging Beam<br>(used as a back brace) |

#### OPTIONAL (ADD THE FOLLOWING KITS FOR STAGING AND RENTALS)

|        |                 |  |
|--------|-----------------|--|
| 2 pcs. | MVFS-025-T-QRP  | 8pc 1/4" Quick Release Pin / lanyard kit |
| 1 pc.  | MVFS-1.5-X1QRP  | 2pc 1/4" Quick Release Pin / lanyard kit |
| 2 pcs. | MVFS-375-ME-QRP | 2pc 3/8" Quick Release Pin / lanyard kit |



Rated for indoor use.

**Adaptive Technologies Group**  
1635 E. Burnett Street | Signal Hill, CA 90755 USA  
Ph: 562.424.1100 | Fax: 562.424.3520  
www.adapttechgroup.com



#### ALWAYS INSTALL SAFETY CABLES

**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.

# Interlocking Flyable LCD Video Wall System


4 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

NEC X551 UN

### ONE-COLUMN RIGGING BEAMS


MAXIMUM OF 8 MONITORS PER COLUMN



#### MVFS-X551-X1RBL (Landscape)

One column rigging beam

|                          |  |
|--------------------------|--|
| <b>Working load:</b>     | Using two inner hang points = 1060 lb./482 |
| <b>KgWorking load:</b>   | Using two outer hang points = 895 lb./407  |
| <b>Kg.Design Factor:</b> | 10:1 ratio                                 |
| <b>Material:</b>         | Alloy Steel tubing                         |
| <b>Finish:</b>           | Powder coat paint                          |
| <b>Color:</b>            | Black                                      |
| <b>Weight:</b>           | 13.1 lb./5.6 Kg                            |
| <b>Shipping weight:</b>  | 21.4 lb./9.7 Kg                            |
| <b>Pack Count:</b>       | One  |



#### MVFS-X551-X1RBP (Portrait)

One column rigging beam

|                          |  |
|--------------------------|--|
| <b>Working load:</b>     | Using two inner hang points = 1060 lb./482 |
| <b>KgWorking load:</b>   | Using two outer hang points = 895 lb./407  |
| <b>Kg.Design Factor:</b> | 10:1 ratio                                 |
| <b>Material:</b>         | Alloy Steel tubing                         |
| <b>Finish:</b>           | Powder coat paint                          |
| <b>Color:</b>            | Black                                      |
| <b>Weight:</b>           | 13.1 lb./5.6 Kg                            |
| <b>Shipping weight:</b>  | 21.4 lb./9.7 Kg                            |
| <b>Pack Count:</b>       | One  |



Rated for indoor use.

#### ALWAYS INSTALL SAFETY CABLES

**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.

# Interlocking Flyable LCD Video Wall System

5 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

## NEC X551 UN

### CONFIGURATIONS

The following configurations represent popular video display patterns, but many more variables are available. Contact our applications department for assistance in designing a custom display that assures a safe and easy to install video wall.

### 2 X 2 Flying Video Wall (Landscape)


#### 2 wide by 2 deep LCD's (8 Deep Maximum)

##### FOR PERMANENT INSTALLATIONS

|        |   |                    |
|--------|---|--------------------|
| 4 pcs. | MVFS-X551-T                               | LCD Frame          |
| 1 pc.  | MVFS-X551-X2RBL                           | 2-Way Rigging Beam |
| 2 pcs. | MVFS-1.5X2-SME                            | Shackle Mount      |
| 2pcs.  | MVFS-X551-X2RBP<br>(used as a back brace) | Rigging Beam       |

##### OPTIONAL (ADD THE FOLLOWING KITS FOR STAGING AND RENTALS)

|        |                 |   |
|--------|-----------------|---|
| 4 pcs. | MVFS-025-T-QRP  | 8pcs 1/4" Quick Release Pin / lanyard kit |
| 1 pc.  | MVFS-1.5-X2QRP  | 4pcs 1/4" Quick Release Pin / lanyard kit |
| 2 pcs. | MVFS-375-ME-QRP | 2pcs 3/8" Quick Release Pin / lanyard kit |



### 2 X 2 Flying Video Wall (Portrait)


#### 2 wide by 2 deep LCD's (8 Deep Maximum)

##### FOR PERMANENT INSTALLATIONS

|        |                 |                                       |
|--------|-----------------|---------------------------------------|
| 4 pcs. | MVFS-X551-T     | LCD Frame                             |
| 1 pc.  | MVFS-X551-X2RBP | 2-Way Rigging Beam                    |
| 2 pcs. | MVFS-1.5X2-SME  | Shackle Mount                         |
| 2pcs.  | MVFS-X551-X2RBL | Rigging Beam<br>used as a back brace) |

##### OPTIONAL (ADD THE FOLLOWING KITS FOR STAGING AND RENTALS)

|        |                 |   |
|--------|-----------------|---|
| pcs.   | MVFS-025-T-QRP  | 8pcs 1/4" Quick Release Pin / lanyard kit |
| 1 pc.  | MVFS-1.5-X2QRP  | 4pcs 1/4" Quick Release Pin / lanyard kit |
| 2 pcs. | MVFS-375-ME-QRP | 2pcs 3/8" Quick Release Pin / lanyard kit |



Rated for indoor use.

**Adaptive Technologies Group**  
1635 E. Burnett Street | Signal Hill, CA 90755 USA  
Ph: 562.424.1100 | Fax: 562.424.3520  
www.adapttechgroup.com



#### ALWAYS INSTALL SAFETY CABLES

**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.



# Interlocking Flyable LCD Video Wall System


6 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

NEC X551 UN

### TWO-COLUMN RIGGING BEAMS


MAXIMUM OF 8 MONITORS PER COLUMN



#### MVFS-X551-X2RBL (Landscape)

Two column rigging beam

|                           |  |
|---------------------------|--|
| <b>Working load:</b>      | Using two inner hang points = 1060 lb./482 |
| <b>KgWorking load:</b>    | Using two outer hang points = 895 lb./407  |
| <b>Kg.Design Factor 1</b> | 0:1 ratio                                  |
| <b>Material:</b>          | Alloy Steel tubing                         |
| <b>Finish:</b>            | Powder coat paint                          |
| <b>Color:</b>             | Black                                      |
| <b>Weight:</b>            | 13.1 lb./5.6 Kg                            |
| <b>Shipping weight:</b>   | 21.4 lb./9.7 Kg                            |
| <b>Pack Count:</b>        | One  |



#### MVFS-X551-X2RBP (Portrait)

Two column rigging beam

|                         |   |
|-------------------------|---|
| <b>Working load:</b>    | Using two hang points (inner and outer)= 982 lb./446.4 kg |
| <b>Design Factor:</b>   | 10:1 ratio  |
| <b>Material:</b>        | Alloy Steel tubing  |
| <b>Finish:</b>          | Powder coat paint   |
| <b>Color:</b>           | Black   |
| <b>Weight:</b>          | 7.25 lb./3.3 Kg   |
| <b>Shipping weight:</b> | 11 lb.  |



Rated for indoor use.

#### ALWAYS INSTALL SAFETY CABLES

**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.

# Interlocking Flyable LCD Video Wall System

7 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

## NEC X551 UN

### CONFIGURATIONS

The following configurations represent popular video display patterns, but many more variables are available. Contact our applications department for assistance in designing a custom display that assures a safe and easy to install video wall.

### 3 X 3 Flying Video Wall(Landscape)


#### 3 wide by 3 deep LCD's (8 Deep Maximum)

FOR PERMANENT INSTALLATIONS

|        |                 |  |
|--------|-----------------|--|
| 9 pcs. | MVFS-X551-T     | LCD Frame                                    |
| 1 pc.  | MVFS-X551-X3RBL | 3-Way Rigging Beam                           |
| 2 pcs. | MVFS-1.5X2-SME  | Shackle Mount                                |
| 2 pcs. | MVFS-X551-X3RBP | 3-Way Rigging Beam<br>(used as a back brace) |

#### OPTIONAL (ADD THE FOLLOWING KITS FOR STAGING AND RENTALS)

|        |                 |   |
|--------|-----------------|---|
| 9 pcs. | MVFS-025-T-QRP  | 8pcs 1/4" Quick Release Pin / lanyard kit |
| 1 pc.  | MVFS-1.5-X3QRP  | 6pcs 1/4" Quick Release Pin / lanyard kit |
| 2 pcs. | MVFS-375-ME-QRP | 2pcs 3/8" Quick Release Pin / lanyard kit |



### 3 X 3 Flying Video Wall (Portrait)


#### 3 wide by 3 deep LCD's (8 Deep Maximum)

FOR PERMANENT INSTALLATIONS

|        |                 |  |
|--------|-----------------|--|
| 9 pcs. | MVFS-X551-T     | LCD Frame                                    |
| 1 pc.  | MVFS-X551-X3RBP | 3-Way Rigging Beam                           |
| 2 pcs. | MVFS-1.5X2-SME  | Shackle Mount                                |
| 2 pcs. | MVFS-X551-X3RBL | 3-Way Rigging Beam<br>(used as a back brace) |

#### OPTIONAL (ADD THE FOLLOWING KITS FOR STAGING AND RENTALS)

|        |                 |   |
|--------|-----------------|---|
| 9 pcs. | MVFS-025-T-QRP  | 8pcs 1/4" Quick Release Pin / lanyard kit |
| 1 pc.  | MVFS-1.5-X3QRP  | 6pcs 1/4" Quick Release Pin / lanyard kit |
| 2 pcs. | MVFS-375-ME-QRP | 2pcs 3/8" Quick Release Pin / lanyard kit |



Rated for indoor use.

**Adaptive Technologies Group**  
1635 E. Burnett Street | Signal Hill, CA 90755 USA  
Ph: 562.424.1100 | Fax: 562.424.3520  
www.adapttechgroup.com



#### ALWAYS INSTALL SAFETY CABLES

**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.

# Interlocking Flyable LCD Video Wall System


8 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

NEC X551 UN

### THREE-COLUMN RIGGING BEAMS


MAXIMUM OF 8 MONITORS PER COLUMN



#### MVFS-X551-X3RBL (Landscape)

Three column rigging beam

|                         |   |
|-------------------------|---|
| <b>Working load:</b>    | Using two hang points (Inner holes)= 1002 lb./455.5 kg. |
| <b>Working load:</b>    | Using Three hang points = 1768 lb./804 Kg.              |
| <b>Design Factor:</b>   | 10:1 ratio  |
| <b>Material:</b>        | Alloy Steel tubing                                      |
| <b>Finish:</b>          | Powder coat paint                                       |
| <b>Color:</b>           | Black   |
| <b>Weight:</b>          | 39.3 lb./17.9 kg.                                       |
| <b>Shipping weight:</b> | 47.6 lb./21.6 Kg.                                       |
| <b>Pack Count:</b>      | One   |



#### MVFS-X551-X3RBP (Portrait)

Three column rigging beam

|                         |  |
|-------------------------|--|
| <b>Working load:</b>    | Using two hang points (inner & outer holes) =1746 lb./794 kg |
| <b>Working load:</b>    | Using three hang points =2964 lb./1347 Kg.                   |
| <b>Design Factor:</b>   | 10:1 ratio   |
| <b>Material:</b>        | Alloy Steel tubing   |
| <b>Finish:</b>          | Powder coat paint  |
| <b>Color:</b>           | Black  |
| <b>Weight:</b>          | 21.92 lb./10 Kg.   |
| <b>Shipping weight:</b> | 30.2 lb/13.7 Kg.   |
| <b>Pack Count:</b>      | One  |



Rated for indoor use.

#### ALWAYS INSTALL SAFETY CABLES

**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.



# Interlocking Flyable LCD Video Wall System

9 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

## NEC X551 UN

### CONFIGURATIONS

The following configurations represent popular video display patterns, but many more variables are available. Contact our applications department for assistance in designing a custom display that assures a safe and easy to install video wall.

### 4 X 4 Flying Video Wall (Landscape)

#### 4 wide by 4 deep LCD's (8 Deep Maximum)


FOR PERMANENT INSTALLATIONS

|         |                 |  |
|---------|-----------------|--|
| 16 pcs. | MVFS-X551-T     | LCD Frame                                    |
| 1 pc.   | MVFS-X551-X4RBL | 4-Way Rigging Beam                           |
| 4 pcs.  | MVFS-1.5X2-SME  | Shackle Mount                                |
| 2 pcs.  | MVFS-X551-X4RBP | 4-Way Rigging Beam<br>(used as a back brace) |

#### OPTIONAL (ADD THE FOLLOWING KITS FOR STAGING AND RENTALS)

|         |                 |   |
|---------|-----------------|---|
| 16 pcs. | MVFS-025-T-QRP  | 8pcs 1/4" Quick Release Pin / lanyard kit |
| 1 pc.   | MVFS-1.5-X4QRP  | 8pcs 1/4" Quick Release Pin / lanyard kit |
| 2 pcs.  | MVFS-375-ME-QRP | 4pcs 3/8" Quick Release Pin / lanyard kit |

Note: 2 pcs. 2-Way Rigging Beams with one MVFS-1.5X2-SMC Beam Connector may also be used in place of the 4-Way Rigging Beam.



### 4 X 3 Flying Video Wall (Portrait)


#### 4 wide by 3 deep LCD's (8 Deep Maximum)

FOR PERMANENT INSTALLATIONS

|         |                 |  |
|---------|-----------------|--|
| 12 pcs. | MVFS-X551-T     | LCD Frame                                    |
| 1 pc.   | MVFS-X551-X4RBP | 4-Way Rigging Beam                           |
| 2 pcs.  | MVFS-1.5X2-SME  | Shackle Mount                                |
| 2 pcs.  | MVFS-X551-X3RBL | 3-Way Rigging Beam<br>(used as a back brace) |

#### OPTIONAL (ADD THE FOLLOWING KITS FOR STAGING AND RENTALS)

|         |                 |   |
|---------|-----------------|---|
| 12 pcs. | MVFS-025-T-QRP  | 8pcs 1/4" Quick Release Pin / lanyard kit |
| 1 pc.   | MVFS-1.5-X4QRP  | 8pcs 1/4" Quick Release Pin / lanyard kit |
| 2 pcs.  | MVFS-375-ME-QRP | 2pcs 3/8" Quick Release Pin / lanyard kit |



Rated for indoor use.

**Adaptive Technologies Group**  
1635 E. Burnett Street | Signal Hill, CA 90755 USA  
Ph: 562.424.1100 | Fax: 562.424.3520  
www.adapttechgroup.com



#### ALWAYS INSTALL SAFETY CABLES

**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.

# Interlocking Flyable LCD Video Wall System


10 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

NEC X551 UN

### FOUR-COLUMN RIGGING BEAMS

MAXIMUM OF 8 MONITORS PER COLUMN



### MVFS-X551-X4RBP (Portrait) Four column rigging beam

|                         |  |
|-------------------------|--|
| <b>Working load:</b>    | Using two hang points (inner holes) = 1181 lb./537 Kg.<br>Using Three hang points (Outer holes) = 1759 lb/799 kg<br>Using four Hang points = 2942 lb./1337 Kg. |
| <b>Design Factor:</b>   | 10:1 ratio   |
| <b>Material:</b>        | Alloy Steel tubing   |
| <b>Finish:</b>          | Powder coat paint  |
| <b>Color:</b>           | Black  |
| <b>Weight:</b>          | 29.3 lb./13.3 Kg.  |
| <b>Shipping weight:</b> | 37.25  |



Rated for indoor use.

#### ALWAYS INSTALL SAFETY CABLES

**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.

# Interlocking Flyable LCD Video Wall System

11 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

## NEC X551 UN

### 5 X 5 Flying Video Wall (Landscape)

#### 5 wide by 5 deep LCD's

FOR PERMANENT INSTALLATIONS


|         |                 |  |
|---------|-----------------|--|
| 25 pcs. | MVFS-X551-T     | LCD Frame                                    |
| 1 pc.   | MVFS-X551-X2RBL | 2-Way Rigging Beam                           |
| 1 pc.   | MVFS-X551-X3RBL | 3-Way Rigging Beam                           |
| 4 pc.   | MVFS-1.5X2-SMC  | Beam Connector                               |
| 4 pcs.  | MVFS-1.5X2-SME  | Shackle Mount                                |
| 3 pcs.  | MVFS-X551-X5RBP | 5-Way Rigging Beam<br>(used as a back brace) |

#### OPTIONAL (ADD THE FOLLOWING KITS FOR STAGING AND RENTALS)

|         |                 |   |
|---------|-----------------|---|
| 25 pcs. | MVFS-025-T-QRP  | 8pcs 1/4" Quick Release Pin / lanyard kit |
| 1 pc.   | MVFS-1.5-X2QR P | 4pcs 1/4" Quick Release Pin / lanyard kit |
| 1 pc.   | MVFS-1.5-X3QR P | 6pcs 1/4" Quick Release Pin / lanyard kit |
| 4 pcs.  | MVFS-375-ME-QRP | 4pcs 3/8" Quick Release Pin / lanyard kit |
| 2 pcs.  | MVFS-375-MC-QRP | 4pcs 3/8" Quick Release Pin / lanyard kit |

### CONFIGURATIONS

The following configurations represent popular video display patterns, but many more variables are available. Contact our applications department for assistance in designing a custom display that assures a safe and easy to install video wall.



### 5 X 3 Flying Video Wall (Portrait)


#### 5 wide by 3 deep LCD's

FOR PERMANENT INSTALLATIONS

|         |                 |  |
|---------|-----------------|--|
| 15 pcs. | MVFS-X551-T     | LCD Frame                                    |
| 1 pc.   | MVFS-X551-X2RBP | 2-Way Rigging Beam                           |
| 1 pc.   | MVFS-X551-X3RBP | 3-Way Rigging Beam                           |
| 3 pcs.  | MVFS-1.5X2-SME  | Shackle Mount                                |
| 1 pc.   | MVFS-1.5X2-SMC  | Beam Connector                               |
| 3 pcs.  | MVFS-X551-X3RBL | 3-Way Rigging Beam<br>(used as a back brace) |

#### OPTIONAL (ADD THE FOLLOWING KITS FOR STAGING AND RENTALS)

|         |                 |  |
|---------|-----------------|--|
| 15 pcs. | MVFS-025-T-QRP  | 8 pcs 1/4" Quick Release Pin / lanyard kit |
| 1 pc.   | MVFS-1.5-X2QRP  | 4 pcs 1/4" Quick Release Pin / lanyard kit |
| 1 pc.   | MVFS-1.5-X3QRP  | 6 pcs 1/4" Quick Release Pin / lanyard kit |
| 3 pcs.  | MVFS-375-ME-QRP | 2 pcs 3/8" Quick Release Pin / lanyard kit |
| 1 pcs.  | MVFS-375-MC-QRP | 4 pcs 3/8" Quick Release Pin / lanyard kit |



Rated for indoor use.

#### ALWAYS INSTALL SAFETY CABLES


**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.

# Interlocking Flyable LCD Video Wall System

12 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

## NEC X551 UN



### DIMENSIONS:

#### MVFS-X551-T LCD Frame

|                         |   |
|-------------------------|---|
| <b>Working Load:</b>    | 264 lb. / 120 Kg  |
| <b>Design Factor:</b>   | 10:1 ratio  |
| <b>Weight:</b>          | 40 lb / 18.2 Kg   |
| <b>Shipping weight:</b> | 45 lb / 20.5 Kg   |
| <b>Pack Count:</b>      | One   |
| <b>Material:</b>        | Steel alloy tubing and high strength aluminum connecting bars |
| <b>Finish:</b>          | Powder coat paint   |
| <b>Color:</b>           | Black   |
| <b>Contents:</b>        | 1 Frame   |

#### MVFS-025-T-QRP 1/4" Quick Release Pin / Lanyard Kit

|                       |  |
|-----------------------|--|
| <b>Working Load:</b>  | 8,200 lb. / 3,727 Kg (double shear)        |
| <b>Design Factor:</b> | 5:1 ratio                                  |
| <b>Material:</b>      | High-strength steel                        |
| <b>Finish:</b>        | Satin                                      |
| <b>Color:</b>         | Silver                                     |
| <b>Contents:</b>      | 8 QRP's / Lanyard assemblies and hardware. |

#### MVFS-1.5-X1QRP 1/4" Quick Release Pin / Lanyard Kit

|                       |  |
|-----------------------|--|
| <b>Working Load:</b>  | 8,200 lb. / 3,727 Kg (double shear)        |
| <b>Design Factor:</b> | 5:1 ratio                                  |
| <b>Material:</b>      | High-strength steel                        |
| <b>Finish:</b>        | Satin                                      |
| <b>Color:</b>         | Silver                                     |
| <b>Contents:</b>      | 2 QRP's / Lanyard assemblies and hardware. |

#### QRP375-25L-4130 3/8" Quick Release Pin

|                       |  |
|-----------------------|--|
| <b>Working Load:</b>  | 18,400 lb. / 8,364 Kg (double shear)       |
| <b>Design Factor:</b> | 5:1 ratio                                  |
| <b>Material:</b>      | High-strength steel                        |
| <b>Finish:</b>        | Satin                                      |
| <b>Color:</b>         | Silver                                     |
| <b>Contents:</b>      | 2 QRP's / Lanyard assemblies and hardware. |

#### MVFS-X551-HNDL \* Replacement X551 Handle

|                  |                      |
|------------------|----------------------|
| <b>Material:</b> | Steel                |
| <b>Finish:</b>   | Vinyl clad over zinc |
| <b>Color:</b>    | Black                |

\* COMES WITH MVFS-X551-T-FRAME



Rated for indoor use.

#### ALWAYS INSTALL SAFETY CABLES


**WARNING:** Mounting and/or suspension of audio and video equipment requires experienced professionals. Improperly installed loudspeakers can result in property damage, personal injury and/or liability to the installing contractor.

# Interlocking Flyable LCD Video Wall System

13 of 13

## MODULAR FLYING VIDEO WALL FRAME SYSTEM

## NEC X551 UN



### DIMENSIONS]

#### MVFS-1.5X2-SME Shackle Mount - Extended

|                         |                           |
|-------------------------|---------------------------|
| <b>Working Load:</b>    | 990 lb. / 450 Kg          |
| <b>Design Factor:</b>   | 0:1 ratio                 |
| <b>Material:</b>        | High-strength steel alloy |
| <b>Finish:</b>          | Powder coat paint         |
| <b>Color:</b>           | Black                     |
| <b>Weight:</b>          | 2.7 lb. / 1.2 Kg          |
| <b>Shipping weight:</b> | 3.3 lb. / 1.5 Kg          |
| <b>Pack Count:</b>      | One                       |

#### MVFS-1.5X2-SMC Rigging Beam Connector – Shackle Mount

|                         |                           |
|-------------------------|---------------------------|
| <b>Working Load:</b>    | 624 lb. / 284 Kg          |
| <b>Design Factor:</b>   | 10:1 ratio                |
| <b>Material:</b>        | High-strength steel alloy |
| <b>Finish:</b>          | Powder coat paint         |
| <b>Color:</b>           | Black                     |
| <b>Weight:</b>          | 9.0 lb. / 4.1 Kg          |
| <b>Shipping weight:</b> | 11.3 lb. / 5.1 Kg         |
| <b>Pack Count:</b>      | One                       |

#### MVFS-X551-FOOT \* Floor Alignment Stand

Two required per column

|                         |                    |
|-------------------------|--------------------|
| <b>Working Load:</b>    | Steel alloy tubing |
| <b>Finish:</b>          | Powder coat paint  |
| <b>Color:</b>           | Black              |
| <b>Weight:</b>          | 9.0 lb. / 4.1 Kg   |
| <b>Shipping weight:</b> | 12 lb. / 5.1       |

**\* THIS IS AN ASSEMBLY FIXTURE ONLY.  
IT IS NOT FOR DISPLAY PURPOSES.**

#### STAND OFF 9-0498\* Adjustable M6 Anchor

|                  |               |
|------------------|---------------|
| <b>Material:</b> | Steel         |
| <b>Finish:</b>   | Zinc Plated   |
| <b>Color:</b>    | Black         |
| <b>QTY:</b>      | 4 per monitor |

**\* COMES WITH MVFS-V601-T-FRAME**



Rated for indoor use.